



Lavabile Extra

Painting for internal use transpiring supercovering

CODE 1029 - 1030



COLOUR White or light colours from chart

PACKAGING Drums litographed of lt 4 and 13

STORAGE 12 months at least in its original packaging far from low and high temperatures

CHARACTERISTICS

LAVABILE EXTRA is a water-based painting for internal use, opaque, transpiring, washable, with high cladding power, excellent degree of whiteness, composed of resins in water emulsion, micronized charges, specific admixtures.

APPLICATION FIELDS

Painting of all internal surfaces, new one or already painted with similar paints, suitable for painting of substrates in gypsum, plasterboard, cementitious or lime based.

APPLICATION PROCEDURE

SUBSTRATES PREPARATION

Substrates have to be fine-finished, cured, perfectly clean, in good conditions, with no detaching parts, oil, grease, dust, humidity, saltpetre or moulds traces. Eventual crumbling surfaces need to be previously consolidated before the product application.

PRODUCT PREPARATION

Dilute Lavabile Extra with 30-35% of clean water for the first coat, 20-25% for the second one, mixing the product with a drill at a low speed rotations, obtaining a dough homogeneous.

PRODUCT APPLICATION

Apply in two or more coats, through brush, wool roller or spray, after application of insulating fixative ALBURESIN, after at least 12-24 hours in normal conditions of temperatures and humidity. Apply the product at temperatures between +5°C and +30°C. Do not apply with UR higher than 85%.

CONSUMPTION

About 0,150 - 0,200 Lt / mq

TECHNICAL DATA

PRODUCT IDENTIFICATION DATA

Consistency	Liquid dense
Colour	White or light colours from chart
Density of the paste	1,69 - 1,75 kg/lt
Brilliance	Opaque

APPLICATIVE DATA

Dilution ratio	30-35% for the first coat 20-25% for the second one
Waiting time between coats	6/8 hours
Time to drying for touch	about 2 hours
Drying time	24-36 hours basing on the environmental temperature and substrate's absorption

FINAL PERFORMANCE

Resistance to chemical attacks: excellent to atmospheric agents and smog.

WARNINGS

Do not apply the product on fresh substrates. Protect all the parts not to dirty.

ITEM SPECIFICATION

Decoration and protection of internal surfaces with white or coloured painting, washable, transpiring, LAVABILE EXTRA of Plastimur s.r.l., composed of resins in water emulsion, micronized charges, specific admixtures. This painting is to apply in two coats, after application of fixative "Alburesin", dilute with 30-35% for the first coat, 20-25% for the second one, with an average consumption of 0,150-0,200 lt/mq.